



Gas flow measuring devices
Ultrasonic gas flow meter, FLOWSIC600

FLOWSIC600 2-path



Model Name > [FLOWSIC600 2-path](#)



The measuring device FLOWSIC600 is an ultrasonic gas flow meter for high performance requirements. The FLOWSIC600 2path type with its two measuring paths is the ideal solution for non-custody transfer applications like process monitoring or internal billing. The compact design with concealed cabling provides a robust, trouble-free and low-maintenance system. The sealed ultrasonic transducers are suitable for applications with dry, wet or corrosive gases. Due to the direct path layout, the signals are not reflected inside the device and thus not influenced by contamination. This results in long-term stability and accuracy of the system. Adjustable impulse outputs or Modbus connections allow the use of installed flow computers.

At a glance

- Direct 2-path layout without reflection of signals
- Bidirectional measurement without pressure loss
- Hermetically sealed ultrasonic transducers made of titanium
- Wide measuring range up to 1:130
- Fully automated, intelligent self-diagnosis
- Integrated logbooks and data logs
- Simple operation and extensive diagnosis via operation software MEPAFLOW600 CBM

Your benefits

- Long-term stable and reliable measurement
- Minimal sensitivity to pressure regulator noise and contamination
- Low maintenance requirements due to intelligent self diagnosis (condition based maintenance, CBM)
- Easy-to-use software which supports all diagnostic features
- Low risk of hardware damage from overload
- Transducers can be replaced under operating pressure
- No mechanical wear

Fields of application

- Non-custody transfer applications in gas industry
- Gas flow metering of natural gas and process gases like N₂, O₂, H₂, CO₂, Cl₂, ethylene, etc.
- For gases with high content of H₂S like sour gas or biogas
- Cryogenic gas applications down to -194 °C

Note

The exact device specifications and performance data of the product may deviate from the information provided here, and depend on the application in which the product is being used and the relevant customer specifications.

Technical data

| | |
|----------------------------|---|
| Measurement principle: | Ultrasonic transit time difference measurement |
| Measured values: | Gas velocity Gas volume Sound velocity Volumetric flow |
| Max. number of measurands: | 2 |
| Measuring ranges: | Gas flow rate: 0 ... 6 m ³ /h/0 ... 100,000 m ³ /h |
| Comment: | Measuring ranges depend on nominal pipe size |
| Process temperature: | -194 ... +280 °C on request -40 ... +180 °C |
| Process pressure: | 0 ... 250 bar (g) 0 ... 450 bar (g) on request |
| Nominal pipe size: | 2 ... 48 " (DN 50 ... DN 1200) |
| Ambient temperature: | -40 ... +60 °C |
| Conformities: | AGA-Report No. 9 API 21.1 OIML D11 OIML R137-1 |
| Remark: | Pattern approval: MID, PTB, NMI, Measurement Canada, GOST ... |
| Ex-approvals IECEx: | EX Gb/Ga Ex d e ib [ia Ga] IIA T4 Gb EX Gb/Ga Ex d e ib [ia Ga] IIC T4 Gb IECEx Gb/Ga Ex d e ib [ia Ga] IIC T4 Gb |
| Ex-approvals ATEX: | II 1/2G EEx de ib [ia] IIA T4 II 1/2G EEx de ib [ia] IIC T4 |
| Ex-approvals USA/Canada: | Class I, Division 1, Groups B, C, D T4; Class I, Division 2, Groups A, B, C, D T4 Class I, Division 1, Groups D T4; Class I, Division 2, Groups D T4 |
| Electrical safety: | CE |
| Enclosure rating: | IP 67 |
| Analog outputs: | 1 output: 4 ... 20 mA, 250 Ω active/passive, electrically isolated |
| Digital outputs: | 3 outputs: 30 V, 100 mA passive, electrically isolated |
| Interfaces: | RS-485 |
| Bus protocol: | HART Modbus ASCII Modbus RTU |
| Operation: | Via meter display and software MEPAFLOW600 |
| Device version: | 2-path version |

Australia

Phone +61 3 9457 0600
1800 33 48 02 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg

Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil

Phone +55 11 3215-4900
E-Mail marketing@sick.com.br

Canada

Phone +1 905 771 14 44
E-Mail information@sick.com

Česká republika

Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China

Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark

Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland

Phone +49 211 5301-301
E-Mail info@sick.de

España

Phone +34 93 480 31 00
E-Mail info@sick.es

France

Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain

Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India

Phone +91-22-4033 8333
E-Mail info@sick-india.com

Israel

Phone +972-4-6881000
E-Mail info@sick-sensors.com

Italia

Phone +39 02 27 43 41
E-Mail info@sick.it

Japan

Phone +81 (0)3 5309 2112
E-Mail support@sick.jp

Magyarország

Phone +36 1 371 2680
E-Mail office@sick.hu

Nederland

Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge

Phone +47 67 81 50 00
E-Mail sick@sick.no

Österreich

Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska

Phone +48 22 837 40 50
E-Mail info@sick.pl

România

Phone +40 356 171 120
E-Mail office@sick.ro

Russia

Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz

Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore

Phone +65 6744 3732
E-Mail sales.gsg@sick.com

Slovenija

Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa

Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea

Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi

Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige

Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan

Phone +886 2 2375-6288
E-Mail sales@sick.com.tw

Türkiye

Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates

Phone +971 (0) 4 88 65 878
E-Mail info@sick.ae

USA/México

Phone +1(952) 941-6780
1 (800) 325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at www.sick.com